

## FUEL OIL 2-P

**APPLICATION:**

Fuel oil 2-P is used as fuel for furnaces.

**PHYSICAL AND CHEMICAL PROPERTIES:**

REQUIREMENTS	UNIT OF MEASURE	VALUE	TEST METHOD
Density at 15 <sup>o</sup> C, max	g/cm <sup>3</sup>	0.891	PN-EN ISO 12185 PN-ISO 3675
Kinematic viscosity at 50 <sup>o</sup> C, max	mm <sup>2</sup> /s	60	PN-EN ISO 3104
Ignition point/temperature, min	<sup>o</sup> C	110	PN-EN ISO 2592
Sulphur content, max	%(m/m)	1.0	PN-EN ISO 8754
Calorific value min	kJ/kg	41 500	PN-86/C-04062
Pour point/temperature, max	<sup>o</sup> C	28	PN-ISO 3016
Foreign solid matter content, max	%(m/m)	0.1	PN-58/C-04089
Ash residue after incineration, max	%(m/m)	0.1	PN-EN ISO 6245
Water extract reaction,	-	neutral	PN-84/C-04064
Water content, max	%(v/v)	1.0	PN-EN ISO 3733
Vacuum distillation, multi-cut composition: up to 350 <sup>o</sup> C distils, max	<sup>o</sup> C	29	ASTM D-1160

**PACKAGES: BULK**
**MADAK TRADE S.R.O.**

sídlem: Nádražní 207/17, Český Těšín, PSČ 737 01, DIČ: CZ28608071,  
společnost zapsaná v obchodní rejstříku vedeném Krajským soudem v Ostravě, oddíl C, číslo vložky: 34395  
[www.madaktrade.cz](http://www.madaktrade.cz), [office@madaktrade.cz](mailto:office@madaktrade.cz)