



FUEL OIL "B"

APPLICATION:

Fuel oil "B" is used as fuel for stoves and to heat asphalt

PHYSICAL AND CHEMICAL PROPERTIES:

REQUIREMENTS	UNIT OF MEASURE	VALUE	TEST METHOD
Density at 15°C, max	g/cm³	typical 0.8	ISO 3675
Kinematic viscosity at 20°C, not higher than	mm²/s	15	EN ISO 3104
Ignition point/temperature, not lower than	°C	56	EN ISO 2719
Sulphur content, not higher than	%(m/m)	0.55	ISO 8754
Calorific value not lower than	KJ/kg	41000	PN-86/C-04062
Pour point/temperature, not higher than	°C	-15	PN 83/C-04117
Carbon residue, not higher than	%(m/m)	0.03	EN ISO 10370
Ash residue after incineration, not higher than	%(m/m)	0.01	EN ISO 6245
Water content, not higher than	mg/kg	500	EN ISO 12937
Normal distillation, multi-cut composition: - up to 250°C distils, not higher than	%(V/V)	64	EN ISO 3405
Normal distillation, multi-cut composition: - up to 3250°C distils, not higher than	%(V/V)	84	EN ISO 3405
Colour	-	red	visual assessment

PACKAGES: BULK

MADAK TRADE S.R.O.

sídlem: Nádražní 207/17, Český Těšín , PSČ 737 01, DIČ: CZ28608071,
společnost zapsaná v obchodní rejstříku vedeném Krajským soudem v Ostravě, oddíl C, číslo vložky: 34395
www.madaktrade.cz, office@madaktrade.cz