

FUEL OIL C3

APPLICATION:

Fuel oil C3 is used as fuel for central heating boilers

PHYSICAL AND CHEMICAL PROPERTIES:

REQUIREMENTS	UNIT OF MEASURE	VALUE	TEST METHOD
Density at 15°C, min	g/cm ³	0.891	EN ISO 12185 PN-ISO 3675
Calorific value min	MJ/kg	39.7	PN-86/C-04062
Ignition point/temperature, min	°C	62	EN ISO 2719
Kinematic viscosity at 100°C,	mm ² /s	55	EN ISO 3104
Pour point/temperature, max	°C	40	PN-83/C-04117
Sulphur content, max	%(m/m)	1.0	EN ISO 8754
Contaminants, max	-	0.5	EN ISO 3735
Water content, max	%(V/V)	1.0	EN ISO 12937
Ash residue after incineration, max	%(m/m)	0.2	EN ISO 6245
Water extract reaction,	-	neutral	PN-84/C-04064
Vanadium content, max	mg/kg	150	PN-77/C-04029

PACKAGES: BULK**MADAK TRADE S.R.O.**

sídlem: Nádražní 207/17, Český Těšín, PSČ 737 01, DIČ: CZ28608071,
společnost zapsaná v obchodní rejstříku vedeném Krajským soudem v Ostravě, oddíl C, číslo vložky: 34395
www.madaktrade.cz, office@madaktrade.cz