

FUEL OIL EKO-A

APPLICATION:

Fuel oil EKO-A is used as fuel for stoves and to heat asphalt

PHYSICAL AND CHEMICAL PROPERTIES:

REQUIREMENTS	UNIT OF MEASURE	VALUE	TEST METHOD
Density at 15 ⁰ C, max	g/cm ³	0.830-0.89	EN ISO 12185 ISO 3675
Kinematic viscosity at 50 ⁰ C, max	mm ² /s	8	EN ISO 3104
Ignition point/temperature, min	⁰ C	62	EN ISO 2719
Sulphur content, max	%(m/m)	0.75	EN ISO 8754
Calorific value min	kJ/kg	42000	PN-86/C-04062
Pour point/temperature, max	⁰ C	0	PN-ISO 3016
Carbon residue, max	%(m/m)	0.1	PN-85/C-04075
Ash residue after incineration, max	%(m/m)	0.01	EN ISO 6245
Water content, max	%(V/V)	0.05	PN-83/C-04523
Multi-cut composition: up to 350 ⁰ C distils, max	⁰ C	79	EN ISO 3405

PACKAGES: BULK**MADAK TRADE S.R.O.**

sídlem: Nádražní 207/17, Český Těšín, PSČ 737 01, DIČ: CZ28608071,
společnost zapsaná v obchodní rejstříku vedeném Krajským soudem v Ostravě, oddíl C, číslo vložky: 34395
www.madaktrade.cz, office@madaktrade.cz