

BASE OIL SN-150-R

APPLICATION:

Base oil SN-150 is intended for use in production of lubricants.

PHYSICAL AND CHEMICAL PROPERTIES:

PROPERTY	UNIT	SPECIFICATION	TEST METHOD*
Appearance	-	Bright & Clear	Visual
Density at 15 °C	kg/m ³	max. 885	ASTM D 4052
Kinematic viscosity at 40°C	mm ² /s	25 - 37	ASTM D 445
Kinematic viscosity at 100°C	mm ² /s	4,5 – 5,5	ASTM D 445
Viscosity index	-	min. 93	ASTM D 2270
Flash point	°C	min. 195	ASTM D 92
Pour point	°C	max. -9	ASTM D 97
Colour	-	max. 1,5	ASTM D 1500
Sulphur, mass	%	1,0	ASTM D 4294
Water content	ppm	max. 150	ASTM D 6304

* - Test method could be replaced by other test method which shall be equal to or more precise than the original one.

PACKAGES: BULK**MADAK TRADE S.R.O.**

sídlem: Nádražní 207/17, Český Těšín, PSČ 737 01, DIČ: CZ28608071,
společnost zapsaná v obchodní rejstříku vedeném Krajským soudem v Ostravě, oddíl C, číslo vložky: 34395
www.madaktrade.cz, office@madaktrade.cz